



GAS EQUIPMENT TECHNOLOGY GROUP

UNITS : SCCM CARBON DIOXIDE DATE : 08-07-1991
TUBE NUMBER : #4(E406) TYPICAL STD CONDITIONS : 1 ATMOS. &70 DEG F
FLOAT NUMBER : 002 GAS TEMPERATURE : 70 DEG F
FLOAT MATERIAL: 316 ST. STL. DELIVERY PRESSURE : 0 PSIG

SCALE READING	FLOW RATE	SCALE READING	FLOW RATE	SCALE READING	FLOW RATE	SCALE READING	FLOW RATE
150.0	1430.67	110.0	1099.92	70.0	742.65	30.0	314.27
149.0	1421.22	109.0	1091.90	69.0	732.59	29.0	303.52
148.0	1411.89	108.0	1083.84	68.0	722.47	28.0	292.81
147.0	1402.67	107.0	1075.75	67.0	712.31	27.0	282.14
146.0	1393.56	106.0	1067.63	66.0	702.09	26.0	271.52
145.0	1384.55	105.0	1059.47	65.0	691.82	25.0	260.96
144.0	1375.63	104.0	1051.28	64.0	681.50	24.0	250.45
143.0	1366.81	103.0	1043.05	63.0	671.13	23.0	240.01
142.0	1358.07	102.0	1034.78	62.0	660.72	22.0	229.63
141.0	1349.41	101.0	1026.46	61.0	650.26	21.0	219.32
140.0	1340.83	100.0	1018.11	60.0	639.75	20.0	209.08
139.0	1332.33	99.0	1009.71	59.0	629.21	19.0	198.93
138.0	1323.89	98.0	1001.26	58.0	618.62	18.0	188.85
137.0	1315.51	97.0	992.76	57.0	607.99	17.0	178.87
136.0	1307.20	96.0	984.22	56.0	597.33	16.0	168.98
135.0	1298.94	95.0	975.63	55.0	586.63	15.0	159.19
134.0	1290.74	94.0	966.98	54.0	575.89	14.0	149.50
133.0	1282.58	93.0	958.29	53.0	565.13	13.0	139.91
132.0	1274.46	92.0	949.54	52.0	554.33	12.0	130.44
131.0	1266.39	91.0	940.74	51.0	543.50	11.0	121.09
130.0	1258.35	90.0	931.88	50.0	532.65	10.0	111.86
129.0	1250.34	89.0	922.96	49.0	521.78	9.0	102.76
128.0	1242.36	88.0	913.99	48.0	510.89	8.0	93.79
127.0	1234.41	87.0	904.97	47.0	499.97	7.0	84.96
126.0	1226.48	86.0	895.89	46.0	489.04	6.0	76.28
125.0	1218.56	85.0	886.74	45.0	478.10	5.0	67.75
124.0	1210.66	84.0	877.55	44.0	467.14		
123.0	1202.78	83.0	868.29	43.0	456.18		
122.0	1194.90	82.0	858.97	42.0	445.21		
121.0	1187.02	81.0	849.60	41.0	434.24		
120.0	1179.15	80.0	840.17	40.0	423.27		
119.0	1171.28	79.0	830.67	39.0	412.30		
118.0	1163.40	78.0	821.12	38.0	401.34		
117.0	1155.52	77.0	811.52	37.0	390.39		
116.0	1147.62	76.0	801.85	36.0	379.45		
115.0	1139.72	75.0	792.12	35.0	368.53		
114.0	1131.80	74.0	782.34	34.0	357.62		
113.0	1123.86	73.0	772.50	33.0	346.74		
112.0	1115.91	72.0	762.61	32.0	335.89		
111.0	1107.93	71.0	752.66	31.0	325.07		