

GasWatch 2

SINGLE GAS PERSONAL MONITOR

Description

The GasWatch 2 is the first single-gas monitor that can be comfortably worn on the wrist like a watch. The GasWatch 2 is a convenient, inexpensive, hands-free method of gas monitoring for personal protection from Oxygen deficiency, Carbon Monoxide or Hydrogen Sulfide. The built-in vibratory, audible, and visual alarms immediately alert the user to a dangerous gas condition.

The GasWatch 2 is controlled by a microprocessor for reliability and advanced capabilities. Some of these advanced capabilities include distinctive audible and visual alarms for dangerous gas conditions and malfunctions, a large digital readout with a manual backlight that also automatically lights in an alarm condition, as well as the display of PEAK, TWA, and STEL readings. The replacement sensors are inexpensive, easily field replaceable, and have a life expectancy of about 2 years.

Equipped with a watch band, optional belt clip, hard hat clip, or alligator clip, the GasWatch 2 can be worn either on the wrist, belt, hard hat, or clipped to protective wear.

The GasWatch 2 will operate for over 3,000 hours on one battery (about 1 year normal use). And yes, the GasWatch 2 even tells the time!

Features

- 3 gases to choose from CO, H₂S, or O₂
- Hands free gas monitoring
- Compact "watch type" design
- Fast, accurate response with digital LCD display
- Fits on your wrist, clothing, belt or hard hat
- Automatic backlight during alarm
- Manual backlight
- Sensor fail alarm
- PEAK hold function (min. and max. values for O₂)
- TWA and STEL function
- Displays current time
- Visual, audible, and vibratory alarms standard
- Over 3,000 hours of operation from 1 battery
- Intrinsically safe, CSA, C/US classified
- 2 year warranty



Applications

- Worker safety
- Refineries
- Petrochemical facilities
- Sewage treatment plants
- Fire services
- Chemical plants
- Tunnels
- Mines
- Hazardous waste sites



MATHESON

ask. .The Gas Professionals™

Model Name	GW – 2X	GW – 2H	GW – 2C
Gas Detected	Oxygen (O ₂)	Hydrogen Sulfide (H ₂ S)	Carbon Monoxide (CO)
Detection Principle	Galvanic cell	Electrochemical cell	Electrochemical cell
Detection Range (Increments)	0 – 40% Vol (0.1% Vol)	0 – 100 ppm (0.5 ppm)	0 – 500 ppm (1 ppm)
Alarm Set Points	Low 19.5% Vol High 23.5% Vol Over 40.0% Vol	1st 10.0 ppm 2nd 30.0 ppm TWA 10.0 ppm STEL 15.0 ppm Over 100.0 ppm	1st 25 ppm 2nd 50 ppm TWA 25 ppm STEL 200 ppm Over 500 ppm
Alarm Types	Gas alarms: 2 level alarm (user adjustable), STEL, TWA, and over alarm Trouble alarms: sensor connection, low battery, circuit error, and calibration range error		
Alarm Methods	Gas alarms: flashing light, intermittent buzzer and pulsing vibratory Trouble alarms: flashing light, intermittent buzzer and trouble type displayed		
Gas Sampling	Diffusion		
Response Time	T90 in 20 seconds (Alarms within 5 seconds when exposed to 12% O ₂)	T90 in 30 seconds	
Accuracy	+/- 0.5% Vol	+/- 1.5 ppm (up to 30 ppm)	+/- 5 ppm (up to 150 ppm)
Power	One coin type lithium battery (CR 2450)		
Continuous Operation	Approximately 3,000 hours with no alarms or backlighting (about 1 year of normal use)		
Safety Rating	CSA classified, "C/US", as intrinsically safe. Class I, Division 1, Groups A, B, C and D. Class I, Zone 0, Group IIC. Temperature code T4		
Dimension Weight	2.5" (W) x 1.7" (H) x 0.9" (D) / 63.5 mm(W) x 43 mm(H) x 23 mm(D) 2 ounces / 60 grams		
Case	High-impact plastic, dust and weather proof		
Attachment Choices	Watchband, alligator clip, belt clip, and hard hat clip		
Operating Temperature and Humidity	-10 to 40°C, (14 to 104° F) below 85% RH (non-condensing)		
Special Functions	<ul style="list-style-type: none"> • LCD manual backlight (automatic lighting during alarm) • STEL, TWA function • Peak hold • Time indication 		
Warranty	Two years material and workmanship		

Ordering Information

Model No.	Description	Model No.	Description
GW-2X	GasWatch 2, 0 - 40% Vol O ₂ with watch band	GW-2CA	GasWatch 2, 0 - 500 ppm CO with alligator clip
GW-2XA	GasWatch 2, 0 - 40% Vol O ₂ with alligator clip	GW-2CB	GasWatch 2, 0 - 500 ppm CO with belt clip
GW-2XB	GasWatch 2, 0 - 40% Vol O ₂ with belt clip	GW-2CH	GasWatch 2, 0 - 500 ppm CO with hard hat clip
GW-2XH	GasWatch 2, 0 - 40% Vol O ₂ with hard hat clip		
GW-2H	GasWatch 2, 0 - 100 ppm H ₂ S with watch band	GasWatch 2 Replacement Sensors	
GW-2HA	GasWatch 2, 0 - 100 ppm H ₂ S with alligator clip	Model No.	Description
GW-2HB	GasWatch 2, 0 - 100 ppm H ₂ S with belt clip	ES-1821	Sensor, Carbon Monoxide
GW-2HH	GasWatch 2, 0 - 100 ppm H ₂ S with hard hat clip	ES-1827	Sensor, Hydrogen Sulfide
GW-2C	GasWatch 2, 0 - 500 ppm CO with watch band	OS-BM2	Sensor, Oxygen

