

Dichlorosilane



Grade	Semicon 2N	ULSI Plus 3N			
Purity, %	99.0(w)	99.9(w)**			
Oxygen + Argon		≤1.0 ppmv			
Nitrogen		≤1.0 ppmv			
Carbon Dioxide		≤1.0 ppmv			
Carbon Monoxide		≤1.0 ppmv			
Methane		≤1.0 ppmv			
Hydrocarbons (C ₂ -C ₄)		≤1.0 ppmv			
Hydrogen Chloride		≤500 ppmw			
Monochlorosilane	≤0.3% w	≤250 ppmw			
Other Chlorosilanes	≤1% w				
Trichlorosilane		≤500 ppmw			
Silicon Tetrachloride		≤200 ppmw			
Resistivity, N-type, ohm-cm	> 200	> 400			
Individual Metals – Al*	≤1.0 ppbw	≤50 ppta			
As*	≤0.2 ppbw	≤50 ppta			
B*	≤0.1 ppbw	≤300 ppta			
P*	≤0.3 ppbw	≤300 ppta			
C*	≤1,000 ppbw	≤300 ppba			
Fe*	≤50 ppbw	≤2 ppbw			
Additional Metals:		Ga*	≤10 ppta	Mn	≤0.2 ppbw
		Sb*	≤10 ppta	Mo	≤0.2 ppbw
		In*	≤10 ppta	Ni	≤0.2 ppbw
		Cr	≤0.2 ppbw	Na	≤0.2 ppbw
		Cu	≤0.2 ppbw	Zn	≤0.2 ppbw
				O*	≤200 ppba

*Total deposited metals

**Total Purity excluding HCl

- A lot analysis is provided for each order.
- Individual analysis is also available upon request.
- Pneumatic valves and JIS connections are available upon request.

CYLINDER	Internal Volume	Liters	41	43.8
	Cylinder Sizes >>		QL	QF
	Content	kg	40.9	43.1
		lbs	90	93
Change Point***	lbs	0.6	0.7	

SHIP	UN Number	UN 2189
	DOT Shipping Name	Dichlorosilane
	DOT Classification	2.3 (Poison Gas)
	DOT Label	POISON GAS, FLAMMABLE GAS
	ECCN #	EAR99
	Harmonized #	2827.39.9050

***Recommended Cylinder Change Point at NTP, based on Phase Break, or the amount of product left in the cylinder when the liquid phase has completely evaporated and only gaseous product is left (estimate based on ideal gas behavior).

TECHNICAL DATA	Cylinder Pressure	8.6 psig
	@NTP	1.7 atm
	Specific Volume	0.24 m ³ /kg
	@NTP	3.83 ft ³ /lb
	CAS No	4109-96-0
	CGA/DISS/JIS	678/636/W22-14L
Molecular Weight	101.01 g/mol	

Vapor Pressure	Temp, °C	0.0	15.5	21.0	32.2	43.3
	Press, psig	-4.1	4.3	8.6	18.1	30.8
	Temp, °F	32	60	70	90	110
RFO Data	Size, mm	0.254	0.3556	0.508	0.762	1.016
	Size, inches	0.010	0.014	0.020	0.030	0.040
	Flow, sccm	553	1056	2178	4860	8379
	Flow, scf/h	1.2	2.2	4.6	10	18

NTP = 21°C or 70°F and 101.3 kPa or 1 atm



MATHESON
TRI-GAS
Electronics