

Halocarbon 32 (Difluoromethane)



Grade	ULSI 4N	ULTIMA 4N8
Purity, %	99.99	99.998
Nitrogen	≤40 ppmv	≤5 ppmv
Oxygen	≤10 ppmv	≤2 ppmv
Carbon Dioxide	≤15 ppmv	≤1 ppmv
Methane	≤2 ppmv	≤1 ppmv
Water	≤5 ppmv	≤1 ppmv
Carbon Tetrafluoride	≤5 ppmv	≤1 ppmv
Other Organics	≤100 ppmv	≤10 ppmv
Carbon Monoxide		≤1 ppmv
Acidity as HF		≤0.1 ppmw

- A lot analysis is provided for each order – Individual analysis is also available upon request.
- Other Organics = H₁₂, H₂₂, H₂₃, H_{134a}

CYLINDER	Internal Volume	Liters	43.8	17.1	7.3
	Cylinder Sizes >>		QF	GF	UF
	Content	lbs	64	25	11
		kg	29.1	11.35	5
	Change Point*	lbs	4.3	1.7	0.7

*Recommended Cylinder Change Point at NTP, based on Phase Break, or the amount of product left in the cylinder when the liquid phase has completely evaporated and only gaseous product is left (estimate based on ideal gas behavior).

SHIP	DOT Shipping Name	Difluoromethane	Shipped as
	DOT Classification	2.1 (Flammable Gas)	Liquefied Gas
	DOT Label	FLAMMABLE GAS	
	UN Number	UN 3252	

TECHNICAL DATA	Cylinder Pressure @NTP	207 psig 15.6 atm
	Specific Volume @NTP	0.45 m ³ /kg 7.2 ft ³ /lb
	CAS No	75-10-5
	CGA/DISS/JIS	350/724/W22-14L
	Molecular Weight	52 g/mol

Vapor Pressure	Temp, °C	0.0	15.5	21.0	32.2	43.3
	Press, psig	102	172	207	279	372
	Temp, °F	32	60	70	90	110

NTP = 21°C or 70°F and 101.3 kPa or 1 atm

Cylinder	Treatment	Nominal Diameter (OD)xHeight*		Material of Construction	
		cm	Inches	Cylinder	Valve
QF	ULTRA-LINE®	23x130/134/143	9x51/52.5/56	CS	SS
GF	ULTRA-LINE®	23x66/70/79	9x26/27.5/31	CS	SS
UF	ULTRA-LINE®	15x51/55/64	6x19/20.5/24	CS	SS

*Height is reported as the distance from the bottom of the cylinder to the cylinder neck/ center of the valve outlet/ top of the handwheel
CS: Carbon Steel SS: Stainless Steel



MATHESON
ask...The Gas Professionals™