



## Model 3030 and 3040 Series Single-Stage High-Purity/High Delivery Pressure Brass Regulators



### Materials of Construction

Gauges:	Chrome plated brass
Body:	Nickel plated brass barstock
Bonnet:	Nickel plated brass
Diaphragm:	—
Piston:	316 stainless steel
Seat:	Kel-F 81
Seals:	Teflon & Viton A

### Specifications

Maximum Inlet Pressure:	3000 psig (20,700 kPa)
Maximum Flow Rate:	Model 3030: 4600 SCFH (2170 SLPM)
(At 2500 psig, N <sub>2</sub> )	Model 3040: 4600 SCFH (2170 SLPM)
Flow Capacity (Cv):	0.06
Operating Temperature:	-15°F to 165°F (-26°C to 74°C)
Porting (Regulator Body):	1/4" NPT Female
Porting Configuration:	2 High, 2 Low
Shipping Weight:	5 lbs

### Description

High-purity brass regulators designed for delivery pressures up to 2500 psig.

### Applications

- Applications requiring delivery pressures up to 2500 psig.
- Delivery of gas to manufacturing processes, charging of systems, purging.

### Design Features/Components

- High-purity brass barstock body
- 316 stainless steel piston
- 2-1/2" inlet and delivery pressure gauges
- Equipped with outlet needle valve
- 1/4" NPTM outlet connection
- Porous metal filter protects seat from contamination
- Panel mountable

### Ordering Information

Part Number*	Delivery Pressure Range	Delivery Pressure Gauge	Cylinder Pressure Gauge
SEQ3030CGA	100-1500 psig	0-2000 psig	0-4000 psig
SEQ3040CGA	100-2500 psig	0-3000 psig	0-4000 psig

\*Note: For ordering, replace letters "CGA" with the valve outlet CGA number for the gas cylinder you are using. Some CGA limitations may apply.

### Options

Part Number	Description
SEQADP0163BO	Bonnet Vent Fitting to 1/8" Hose
SEQADP0162BO	Bonnet Vent Adapter to 1/8" FNPT
SEQKIT0204SA	Bonnet Panel Mounting Kit