



Models 3359 MicroMATE™ Portable Cylinder Regulator Stainless Steel Preset Flow Rate Regulator



Description/Applications

Preset flow rate regulators for use with MicroMAT™ 58 cylinders. For use in the calibration of gas detection instrumentation.

Design Features

- Stainless steel body
- Stainless steel pistons
- Hose barb outlet – 3/16"
- Control Knob on/off
- 0.3 SLPM standard preset flow rate; also available: 0.5, 1.0, 1.5, 2.5 SLPM
- 30 psig delivery pressure

Materials of Construction

Body:	316 stainless steel
Piston:	316 stainless steel
Seat:	Teflon
Seals:	Viton
Gauge:	316 stainless steel

Ordering Information

Model Number*	Description
3359-C10	3359 Regulator with C10 Fitting and 0.3 SLPM Flow Rate
3359-C10C	3359 Regulator with C10 Fitting and 0.5 SLPM Flow Rate
3359-C10E	3359 Regulator with C10 Fitting and 1.0 SLPM Flow Rate
3359-C10F	3359 Regulator with C10 Fitting and 1.5 SLPM Flow Rate
3359-C10G	3359 Regulator with C10 Fitting and 2.5 SLPM Flow Rate

*Models available with other CGA's

Accessories

Model Number	Description
MicroMATE™ Accessory Kit	
CKIT-GENL	Complete MicroMATE™ Accessory Kit, Including Carrying Case, Tygon Tubing with Sensor Head Assembly, and Wrench (individual components listed below)

Individual Kit Components

CAS-0030-XX	Carrying Case
TBG-0077-QF	Tygon Tubing
SEN-0021-PD	Sensor Head Assembly
WRC-0013-XX	Wrench