



## Model DR492 Series Vacuum Actuated Regulators



### Description

This simple-to-use regulator makes calibration quick and easy by eliminating the need for sample bags, syringes, canisters, flow meters, or special operator training. Simply connect to the calibration gas cylinder, and from the instrument sample pump inlet to the outlet of the regulator.

### Applications

Ideal for use with instruments that utilize a sample pump to draw the calibration gas. The regulator provides the exact amount of gas that the instrument pump requires.

### Design Features/Components

- Two stage regulator for stable output
- Vacuum actuation pressure – 3" H<sub>2</sub>O
- Standard model supplied with C10 in, 3/16" hose barb out

### Materials of Construction

Body:	Aluminum
Bonnet:	Aluminum
Diaphragm:	Viton
Piston Seals:	Viton
Piston:	303 SS
Main Valve Seat:	Viton and Teflon

### Specifications

Maximum Inlet Pressure:	3000 psig (20,700 kPa)
Porting (Regulator Body):	1/4" FNPT
Porting (Outlet Body):	1/8" FNPT
Flow Capacity:	Up to 3 Lpm @ 3" H <sub>2</sub> O

### Ordering Information

Part Number*	Inlet	Delivery Pressure Range	Cylinder Pressure Gauge
SEQDR492AVC10H	C10	3" H <sub>2</sub> O	0-3000 psig
SEQDR492AVCGAH	CGA	3" H <sub>2</sub> O	0-3000 psig
SEQDR492AV4PFH	1/4" NPTF	3" H <sub>2</sub> O	0-3000 psig

\*Note: For ordering, replace letters "CGA" with the valve outlet CGA number for the gas cylinder you are using. Some CGA limitations may apply.