


### Rotameters

### Model FM-1000 Series

## Compact High Accuracy Flowmeter (65mm)



### Description

The FM-1000 Series Flowmeters incorporate the innovative design of the FM-1050 in a more compact unit without reducing standards of accuracy. This is the rotameter of choice for those interested in conserving space. The same  $\pm 5\%$  full scale accuracy is guaranteed for the 65mm scale length of these flowmeters.

Unlike the FM-1050 series which uses reference scales, the FM-1000 Series flowmeters are direct reading for air, and are available in either English or Metric units. Choose between a black glass or a stainless steel float. These flow tubes are fluted to provide better float stability.

The FM-1000 Series glass metering tubes are enclosed in the Tube-Cube<sup>®</sup>. Protection of the tube, magnified tube scale for easy reading and alignment during replacement are afforded with this unitized holder. Integral fluted float guides for optimum float performance are standard with all tubes unless otherwise specified.

### **Valve Options**

- No valve for those who just want indication
- Utility (six-turn) valve for those who desire control as well as indication
- High accuracy (fifteen-turn) valve for very precise control

### **Design Features**

- Rugged, compact design
- Precision tapered, fluted metering tube
- Tube Cube® unitized glass tube holding assembly
- Reflective plastic background and 1.5 X magnification lens for excellent readability
- Safety blow-out back panel
- Full 10 to 1 (100% to 10% full scale) metering range
- Low pressure drop for increased flow rates at low feed pressures
- Easy installation and quick service access

- Optional utility and high performance valves do not require special fittings
- Corrosion resistant options: all wetted parts of 316 stainless steel or Monel with Viton or Teflon seals
- · Custom scales and flow curves available

### **Specifications**

Repeatability:

Float Materials:

Pressure Rating: 250 psig maximum operating

pressure

Temperature Rating: 250°F maximum operating

temperature

±5% of full scale flow rate – Accuracy:

consult factory for higher accuracies

0.25% of scale reading

10 to 1, i.e., 100% to 10% of full scale Range: Scale Readings: Direct reading air (special other

scales available)

Shipping Weight: 1 lb

### **Materials of Construction**

Wetted End Blocks, Fittings

and Internal Parts: Brass, 316 stainless steel – standard;

Anodized aluminum, Kynar, Monel

optional

Seal Materials: Buna-N or Viton - standard;

Teflon, EPR, or Kalrez - optional Painted or anodized aluminum

Side Plates: Metering Tube: Borosilicate glass enclosed in

Tube-Cube® holder

Piping Connections: Brass, 316 stainless steel - standard;

> Aluminum, Monel - optional Black glass or 316 stainless steel standard; sapphire, ceramic,

Carboloy or Tantalum – optional

Ceramic ink on glass tube, length Scale:

65mm

### **Dimensions FM-1000 Flowmeter**

See pages 369 for engineering drawing.

#### Don't See It Here?

Matheson offers a complete line of variable area flowmeters. Our standard, more common configuration options are shown here. However, if you don't see what you are looking for, contact us. We manufacture flowmeters for liquids as well as gases, and can use other end block materials, such as aluminum, Kynar and Monel, and other seal materials such as Teflon, EPR and Kalrez. In addition, we offer other connection fittings, including NPT, tube and hose, in a variety of sizes. Lastly, we have an enormous library of flow calibrations and correlation tables for dozens of other gases and a wide range of conditions.

So, if you don't see it here, give us a call. We'll build to suit your specific needs.

- See pages 351 for additional general information.
- See page 355 for Tube-Cube® information.
- See page 364 for Replacement Seal Kits and Parts.

# Rotameters



# **Model FM-1000 Series**

## Compact High Accuracy Flowmeter (65mm) (continued)

Flow Tube Capacities for FM-1000 Series Flowmeters, Direct Reading

	Me	tric Scale	Eng	lish Scale	Utility	HA
Float Material	Tube No	Air (SLPM)*	Tube No.	Air (SCFH)*	Valve Sizet	Valve Sizet
Glass	J009	10-130ccm	J011	0.02-0.24	7	2
Stainless Steel	J010	20-300ccm	J012	0.05-0.65	7	2
Glass	J109	100-500ccm	J111	0.2-1.1	7	3
Stainless Steel	J110	200-1000ccm	J112	0.4-2.2	7	3
Glass	J209	0.1-1	J211	0.2-2.8	8	4
Stainless Steel	J210	0.1-2.1	J212	0.2-4.4	8	4
Glass	J409	0.5-5	J411	1-11	8	5
Stainless Steel	J410	0.5-9.5	J412	2-20	8	6
Glass	J509	2-24	J512	5-55	9	6
Stainless Steel	J510	2-50	J513	10-100	9	6
Carboloy	J511	5-70	J514	10-150	9	6

<sup>\*</sup>All air flow rates are at 70°F and 14.7 psia

<sup>†</sup>At 10 psig inlet pressure

Ordering Information								
	Model Series	Number of Metering Tubes	End Blocks/ Seal Material	Valve Types	Connections	Accessories	Connection Orientation	Flow Tube (Capacities)

### Model Number Generator For FM-1000 Series Glass Tube Flowmeters

### **MODEL SERIES**

J = Model FM-1000 Glass Tube Flowmeter with 65mm tube

### **NUMBER OF METERING TUBES**

1 = Single Tube Unit

### END BLOCKS/SEAL MATERIAL

- 3 = Chrome Plated Brass with Buna-N Seals
- 4 = 316 Stainless Steel with Viton Seal

### **VALVE TYPES**

A= Utility Valve on Inlet

B = Utility Valve on Outlet

C=High Accuracy Valve on Inlet

D=High Accuracy Valve on Outlet

G= No Valve

#### CONNECTIONS

1 = 1/8" NPT Female (std)

2 = 1/4" NPT Female

4 = 1/4'' Tube

6 = 1/4" Hose (3/16"-3/8" Hose Tapered)

### ACCESSORIES (ORDER SEPARATELY)

0 = None

1 = Flush Panel Mounting Bezel – Clear

5 = Base Plate

7 = Flush Panel Mounting Bezel – Black

### **CONNECTION ORIENTATION**

1 = Back In and Back Out

### FLOW TUBE (CAPACITIES)

JXXX = See Capacity Table For FM-1000 Series Flowmeters

### **ADDITIONAL OPTIONS**

- +/- 1% Accuracy, Full Scale, With Certification, Gases, Reference Scales
- +/- 5% Accuracy, Full Scale with Certification, Gases, Direct Read
- MMSP-0003-XX Clean for O<sub>2</sub> Service

The FM-1000 Series are direct reading scale flowmeters for air. Inquire for other tube scales available.