



Models RFM-0029-XX and RFM-0030-XX MicroMATE™ Portable Cylinder Regulators Low Flow / Low Pressure Aluminum Regulator



*RFM-0030-XX
(without flowmeter)*

Description/Applications

Aluminum regulators for use with MiniMAT™ cylinders. Air monitoring for PEL and LEL levels.

Design Features/Components

- Aluminum body
- Hose barb outlet – 1/4"
- 30 psig delivery pressure
- Available with 0-1.5 SLPM adjustable flow rate and flowmeter (RFM-0029-XX), 0.5 SLPM preset flow rate (RFM-0030-XX)

Materials of Construction

Body:	Anodized aluminum
Diaphragm:	316 stainless steel
Seat:	Teflon PFA
Seals:	Teflon
Gauge:	316 stainless steel

Ordering Information

Model Number	Description	Use with these Cylinders	Cylinder Pressure	Cylinder Outlet Connection	Cylinder Pressure Gauge
RFM-0029-XX	RFM Regulator with flowmeter	MiniMAT™, MiniMAT™-MS	1800 psig	CGA 180	0-3000 psig
RFM-0030-XX	RFM Regulator with 0.5 SLPM preset flow rate	MiniMAT™, MiniMAT™-MS	1800 psig	CGA 180	0-3000 psig