



### CO<sub>2</sub> Secondary Regulator In-line Brass Regulator

In-line regulator for use with carbon dioxide or mixed gas.

#### Applications:

- Regulates the pressure from the primary gas supply regulator to the beer taps

#### Design Features/Components:

- Forged brass body
- Chrome plated finish
- Nickel-plated valve seats for high corrosion resistance
- Constant pressure supply at high output flow rates
- Easy to use dial knob for pressure adjustment

#### Specifications:

Type:	Secondary Regulator - CO <sub>2</sub> or Mixed Gas
Installation:	Wall mount bracket
Dimensions:	4-3/4" wide x 6-7/8" high x 4-3/4" deep
Performance:	1 Pressure / 1 Keg
Capacity:	SCFM 3.5 Max
Outlet Barb:	3/8" O.D. (to fit 5/16" I.D. Gas Hose)

#### Ordering Information

Part Number	Outlet Pressure Gauge
<b>MIC 1161</b>	0-60 psig

### Model M1-540-15FM Single-Stage Flowmeter Regulator

#### Applications:

- Flowmeter Regulator used for micro-oxygenation applications

#### Design Features/Components:

- Chrome-plated brass body with all brass high-pressure chamber
- Maximum rated inlet pressure 3000 psi
- Durable neoprene diaphragm
- Internal reseating relief valve protects against over-pressurization
- Sintered filter for additional safety and extended regulator life
- 2" diameter gauge
- Polycarbonate inner and outer tubes provide greater accuracy and durability

#### Ordering Information

Part Number	Model Number	Stage	Gauge	Gas	Inlet	Flow Range
<b>WES M1-540-15FM</b>	M1-540-15FM	Single	2" Chrome-plated Brass	Oxygen	CGA 540	1/2 - 15 LPM

