



### Goodyear Vintner® Hose

For handling in-plant and/or tank transfer of beer.

- **Construction Tube:** White Chlorobutyl (FDA/USDA compliant and conforms to 3-A Sanitary Standard 18-03)
- **Cover:** Gray Versigard® synthetic rubber (wrapped) / purple branding tape
- **Reinforcement:** Spiral-plyed synthetic fabric with Monofilament Helix
- **Temperature Range:** -30°F to 220°F
- **Packaging:** Sold per foot; maximum 100' length

#### Ordering Information

| Part Number         | Inside Diameter | Nominal Outside Diameter | Maximum Working Pressure | Bend Radius | Vacuum HG | Weight     |
|---------------------|-----------------|--------------------------|--------------------------|-------------|-----------|------------|
| <b>GDY 20020354</b> | 1"              | 1.62"                    | 250 psi                  | 3"          | 27"       | 0.71 LB/FT |
| <b>GDY 20020356</b> | 1-1/2"          | 2.11"                    | 250 psi                  | 4"          | 27"       | 0.98 LB/FT |
| <b>GDY 20020361</b> | 2"              | 2.68"                    | 250 psi                  | 7"          | 27"       | 1.38 LB/FT |



### Goodyear Gorilla® Wash Down Hose

A multi-purpose industrial hose for high pressure wash down.

- **Construction Tube:** Nitrile synthetic rubber, RMA Class A (High Oil Resistance)
- **Cover:** Yellow Carbryn™ synthetic rubber, RMA Class A (High Oil Resistance) MSHA approved
- **Reinforcement:** Spiral Flexten® yarn, 2" is braided synthetic yarn
- **Temperature Range:** -20°F to 190°F
- **Packaging:** Sold per foot; maximum 500' length

#### Ordering Information

| Part Number         | Inside Diameter | Nominal Outside Diameter | Maximum Working Pressure | Bend Radius | Weight     |
|---------------------|-----------------|--------------------------|--------------------------|-------------|------------|
| <b>GDY 20025701</b> | 3/4"            | 1.19"                    | 500 psi                  | 3"          | 0.41 LB/FT |



### Goodyear Horizon® Wash Down Hose

A multi-purpose industrial hose for medium pressure wash down.

- **Construction Tube:** Versigard® synthetic rubber, RMA class C (Limited Resistance)
- **Cover:** Red Versigard® synthetic rubber
- **Reinforcement:** Spiral synthetic yarn
- **Temperature Range:** -40°F to 190°F
- **Packaging:** Sold per foot; maximum 500' length

#### Ordering Information

| Part Number         | Inside Diameter | Nominal Outside Diameter | Maximum Working Pressure | Weight     |
|---------------------|-----------------|--------------------------|--------------------------|------------|
| <b>GDY 20026290</b> | 3/4"            | 1.12"                    | 200 psi                  | 0.34 LB/FT |

