

Hoses




Continental Vintner™ Reserve Hose

Primarily used for liquid transfer in breweries.

- **Construction Tube:** White Chlorobutyl tube won't impart rubbery tastes or smells
- **Cover:** Gray EPDM synthetic rubber (wrapped)
- **Reinforcement:** Spiral-plyed synthetic fabric with monofilament helix
- **Working/Burst Pressure:** 250 PSI/1000 PSI
- **Temperature Range:** -30°F to 220°F
- **Packaging:** Sold per foot; maximum 100' length

Ordering Information

Part Number	Inside Diameter	Outside Diameter	Working Pressure	Bend Radius	Vacuum HG	Weight
CTT 20943391	1"	1.56"	250 psi	3"	27"	0.60 lb/ft
CTT 20943392	1-1/2"	2.06"	250 psi	4"	27"	0.83 lb/ft
CTT 20943393	2"	2.61"	250 psi	7"	27"	1.18 lb/ft



Continental Pliovic® Plus Hose

Lightweight, economical general purpose hose for carrying air, water and many spray solutions.

- **Construction Tube:** Pliovic®, ARPM Class B (Medium Oil Resistance)
- **Cover:** Blue, Pliovic®, ARPM Class B (Medium Oil Resistance)
- **Reinforcement:** Spiral synthetic yarn
- **Working/Burst Pressure:** 250 PSI/1000 PSI
- **Temperature Range:** -10°F to 158°F
- **Packaging:** Sold per foot; maximum 450' length

Ordering Information

Part Number	Inside Diameter	Outside Diameter	Working Pressure	Bend Radius	Vacuum HG	Weight
GDY 20012678	3/4"	1.11"	250 psi	3"	27"	0.28 lb/ft



Continental Horizon Wash Down Hose

A multi-purpose industrial hose for medium pressure wash down.

- **Construction Tube:** Versigard synthetic rubber, RMA class C (Limited Resistance)
- **Cover:** Red Versigard synthetic rubber
- **Reinforcement:** Spiral synthetic yarn
- **Temperature Range:** -40°F to 190°F
- **Packaging:** Sold per foot; maximum 500' length

Ordering Information


Part Number	Inside Diameter	Nominal Outside Diameter	Maximum Working Pressure	Weight
GDY 20026290	3/4"	1.12"	200 psi	0.34 lb/ft



MATHESON

The Gas Professionals

www.mathesongas.com • 877-684-4427




Kanaflex 210 HFG Suction Hose

Heavy-duty food grade suction hose for bottling and pressure transfer.

- **Construction:** Produced entirely of compounds in compliance with FDA and 3-A nontoxic specifications, flexible PVC, rigid PVC helix, smooth bore, and smooth O.D.
- **Temperature Range:** -13°F to 140°F
- **Packaging:** Sold per foot; maximum 100' length

Ordering Information

Part Number	Inside Diameter	Nominal Outside Diameter	Pitch	Minimum Bend Radius (72° F)	Working Pressure (72° F)	Vacuum Rating (72° F, in HG)	Weight
KAN 210HFG1	1"	1.25"	0.22"	1.9"	86 psi	29.8	0.26 lb/ft
KAN 210HFG112	1-1/2"	1.82"	0.30"	2.8"	72 psi	29.8	0.44 lb/ft
KAN 210HFG2	2"	2.39"	0.33"	3.9"	72 psi	29.8	0.74 lb/ft
KAN 210HFG4	4"	4.53"	0.43"	9.1"	55 psi	29.8	2.01 lb/ft



Kanaflex Kanaline FW Suction and Discharge Hose

Heavy-duty food grade suction and discharge hose for bottling and pressure transfer.

- **Construction:** Produced entirely of compounds in compliance with FDA and 3-A nontoxic specifications, flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, and corrugated O.D.
- **Temperature Range:** -13°F to 140°F
- **Packaging:** Sold per foot; maximum 100' length

Ordering Information

Part Number	Inside Diameter	Nominal Outside Diameter	Pitch	Minimum Bend Radius (72° F)	Working Pressure (72° F)	Vacuum Rating (72° F, in HG)	Weight
KAN FW11/2	1-1/2"	2.03"	0.39"	2.5"	110 psi	28.0	0.56 lb/ft
KAN FW2	2"	2.60"	0.41"	4.0"	100 psi	28.0	0.75 lb/ft
KAN FW3	3"	3.70"	0.59"	6.3"	100 psi	28.0	1.20 lb/ft
KAN FW4	4"	4.78"	0.65"	7.1"	75 psi	28.0	1.74 lb/ft



Kanaflex Banding Coil

Food grade PVC banding coil designed to fit the corrugation of the Kanaline FW suction and discharge hose. Provides a smooth surface for banding. Sold per foot.

Ordering Information

Part Number	Nominal Outside Diameter
KAN BANCOIL11/2	1-1/2"
KAN BANCOIL2	2"
KAN BANCOIL3	3"
KAN BANCOIL4	4"





Unisource Series 2700 Suction and Discharge Hose

Multi-purpose suction and discharge hose designed to handle a variety of transfer applications.

- **Construction Tube:** White Nitrile (FDA, 3-A, USDA compliant)
- **Cover:** Gray Nitrile / PVC Cover
- **Reinforcement:** Multiple textile plies with dual wire helix
- **Temperature Range:** -25°F to +230°F
- **Packaging:** Sold per foot; maximum 100' length

Ordering Information

Part Number	Inside Diameter	Outside Diameter	Working Pressure	Bend Radius	Weight
UNS 2720100	1"	1.46"	150 psi	3"	0.58 lb/ft
UNS 2720150	1-1/2"	1.97"	150 psi	4"	0.85 lb/ft
UNS 2720200	2"	2.48"	150 psi	4.5"	1.22 lb/ft



Unisource Series 2179 Washdown Hose

Multi-purpose white hose for cold and hot water washing.

- **Construction Tube:** Black EPDM (ARPM Class C ORS)
- **Cover:** White EPDM (ARPM Class C ORS)
- **Reinforcement:** Multiple polyester spirals
- **Temperature Range:** -40°F to +200°F
- **Packaging:** Sold per foot; maximum 500' length

Ordering Information

Part Number	Inside Diameter	Outside Diameter	Working Pressure	Weight
UNS 217934	3/4"	1.17"	300 psi	0.42 lb/ft



Unisource Series 1100 Clear Braided Tubing

Used as sight tubing.

- **Construction Tube:** Clear non-toxic PVC (FDA Approved)
- **Reinforcement:** Multiple textile braid
- **Temperature Range:** -25°F to 150°F
- **Packaging:** Sold per foot; maximum 100' length

Ordering Information

Part Number	Inside Diameter	Outside Diameter	Working Pressure	Weight
UNS 1100-25-100	1/4"	.468"	250 PSI	.05 lb/ft
UNS 1100-38-100	3/8"	.595"	225 PSI	.10 lb/ft
UNS 1100-50-100	1/2"	0.75	200 PSI	.13 lb/ft
UNS 1100-750	3/4"	1.030"	150 PSI	.19 lb/ft

