



MATHESON

Nanochem® GuardBed™


Manufactured for MATHESON by  SulfaTrap™

Products For Liquid Fuels

MATHESON offers a number of sorbents for desulfurization of liquid hydrocarbon fuels, such as logistics fuel (e.g., JP-8, JP-5) and diesel. Our sorbents remove sulfur either directly from the liquid stream or from the reformat gas to sub-ppm levels. Additionally, widely available liquid fuels can present an array of sulfur species with varying concentrations. For example, Ultra-Low-Sulfur-Diesel is limited to 15 ppm sulfur while JP-8 may contain as high as 3000 ppm. Combined with a wide variety of hydrocarbon compositions, the situation can overwhelm typical desulfurization systems. **Nanochem® GuardBed™** materials have been designed to overcome these challenges and provide desulfurized fuels under nearly any process condition.

Nanochem® GuardBed™-D1 can be operated as an expendable bed for low sulfur fuels (e.g., ultra low sulfur road diesel), or as a regenerable bed by applying a mild temperature swing for high sulfur fuel such as jet fuel.

Nanochem® GuardBed™-WG and **Nanochem® GuardBed™-HRG** can either be used as stand-alone desulfurizers or in combination with the **Nanochem® GuardBed™-D1** sorbent as a polisher to enhance fuel cleanliness. With high temperature operation, these sorbents excel downstream of reformers with no slippage or moisture dependence.



FEATURES

- **High selectivity** and removal efficiency to all sulfur species
Nanochem® GuardBed™-D1 reduce sulfur levels to less than 40 ppbv in liquid fuels
- **Nanochem® GuardBed™-WG** and **Nanochem® GuardBed™-HRG** reduce sulfur levels to less than 5 ppbv in the reformat gas
- **High capacity**
 - **Nanochem® GuardBed™-D1** achieves ~5 mL/mL capacity in regenerable operation and greater than 12 mL/mL capacity during expendable operation
 - **Nanochem® GuardBed™-WG** removes 48 g sulfur per mL of sorbent
- **Regenerable operation** - oxidizing, reducing, or inert gases can be used for regeneration

Product	Application
Nanochem® GuardBed™-D1	Liquid-phase desulfurization sorbent
Nanochem® GuardBed™-WG	Warm gas desulfurization, 200-650°C
Nanochem® GuardBed™-HRG	Hot reformat gas desulfurization, 500-800°C

Copyright 2022 Matheson Tri-Gas, Inc. All Rights Reserved.

All contents of this document are subject to change without notice and do not represent a commitment on the part of Matheson Tri-Gas, Inc. Every effort is made to ensure the accuracy of this information. However, due to differences in actual and ongoing operational processes and product improvements and revisions, Matheson Tri-Gas, Inc. cannot guarantee the accuracy of this material, nor can it accept responsibility for errors or omissions. This document is intended to serve as a general orientation and cannot be relied upon for a specific operation. No warranties of any nature are extended by the information contained in these copyrighted materials.

All names, products, and services mentioned herein are the trademarks or registered trademarks of their respective organizations and are the sole property of their respective owners. Matheson and the Matheson logo are registered trademarks of Matheson Tri-Gas, Inc.



MATHESON
The Gas Professionals

www.mathesongas.com/purification
email: purification@mathesongas.com
800-828-4313