



1,3-Butadiene

Description

Synonym: Divinyl, Vinylethylene, Biethylene
 Formula: C_4H_6

Gas Data

Molecular Weight: 54.09
 Density: 2.3 kg/m³ @ 21.1°C, 101.325 kPa
 0.14 lb/ft³ @ 70°F, 14.696 psia
 Specific Volume: 0.43 m³/kg @ 21.1°C, 101.325 kPa
 6.9 ft³/lb @ 70°F, 14.696 psia

Safety Information

LFL in Air: 2%
 UFL in Air: 12%
 Permissible Exposure Limit (TLV): 2 ppm

Shipping Information

CAS Registry Number: 106-99-0
 UN Number: UN 1010
 ECCN Number: 1C982
 DOT Proper Shipping Name: Butadienes, Inhibited
 DOT Classification: 2.1 (Flammable Gas)
 DOT Label: FLAMMABLE GAS
 TC Shipping Name: Butadienes, Inhibited
 TC Classification: 2.1
 TC Label: FLAMMABLE GAS

Cylinder Specifications

Cylinder Size	Valve Outlet CGA No.	Pressure psig @ 70°F	Pressure kPa @ 21.1°C	Approximate Ship Weight	
				lb	kg
2	510	21	147	91	41
3	510	21	147	46	21
LB	170	21	147	6	3

Gas Grade Purity Specifications	Product Code	Cylinder Size	Content		Equipment Recommendations	Model No.
			US	Metric		
1,3-Butadiene, CP Grade 99%	G1311140	2	17 lb	7.71 kg	Single Stage Reg. Tee Purge LB Regulator Detector Tube Outlet Plug Wrench	Series 18-510 4753-510 Series 3320-170 8014-168SC TW-4*
	G1311150	3	7 lb	3.18 kg		
	G1311175	LB	0.375 lb	170 gm		

Liquid phase, weight/weight%
 A Certificate of Conformance will be provided on request.
 By request, all except LB can be furnished with full length eductor tubes for liquid withdrawal.
 Please inquire for impurity specifications.
 *Except LB

⚠WARNING: This product can expose you to chemicals including 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.