

# Argon

Ar

Grade	Semicon 5N	ULSI 6N
Purity, %	99.999	99.9999
Oxygen	≤1.0 ppmv	≤300 ppbv
Nitrogen		≤700 ppbv
Carbon Dioxide	≤0.5 ppmv	≤100 ppbv
Carbon Monoxide	≤0.5 ppmv	≤100 ppbv
Methane	≤0.5 ppmv	≤100 ppbv
Water	≤3.0 ppmv	≤500 ppbv

- A lot analysis is provided for each order. – Individual analysis is also available upon request.
- Pneumatic valves and JIS connections are available upon request.

CYLINDER	Internal Volume	Liters	43.8	2.3
	<b>Cylinder Sizes &gt;&gt;</b>		<b>QF/QA</b>	<b>JF/JA/JB</b>
	Content	Liters	7,930	340
		ft <sup>3</sup>	280	12
	Cylinder Pressure*	psig	2,490	2,000
atm		176.1	141.6	

\* @ NTP

SHIP	DOT Shipping Name	Argon, Compressed	UN Number	UN 1006	Shipped as
	DOT Classification	2.2 (Non-Flammable Gas)	ECCN#	EAR99	Compressed Gas
	DOT Label	NON-FLAMMABLE GAS	Harmonized #	2804.21.0000	

TECHNICAL DATA	Specific Volume	0.604 m <sup>3</sup> /kg
	@NTP	9.68 ft <sup>3</sup> /lb
	CAS No	7440-37-1
	CGA/DISS/JIS	580/718/22-14R
	Atomic Weight	39.95 g/mol

Critical Temperature	-122.4°C	-188.4°F
Critical Pressure	50 atm	711.5 psia

NTP = 21°C or 70°F and 101.3 kPa or 1 atm

Cylinder	Treatment	Nominal Diameter (OD)xHeight*		Material of Construction	
		cm	Inches	Cylinder	Valve
QF	ULTRA-LINE®	23x130/134/143	9x51/52.5/56	CS	SS
QA	ULTRA-LINE®	23x130/134/143	9x51/52.5/56	CS	Brass
JF	ULTRA-LINE®	10x33/37/46	4x13/14.5/18	CS	SS
JA	ULTRA-LINE®	10x33/37/46	4x13/14.5/18	CS	Brass
JB	ULTRA-LINE II®	10x33/37/46	4x13/14.5/18	CS	SS

\*Height is reported as the distance from the bottom of the cylinder to the cylinder neck/ center of the valve outlet/ top of the handwheel  
CS: Carbon Steel SS: Stainless Steel

⚠WARNING: This product can expose you to chemicals including Carbon Monoxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

