## **Carbon Dioxide**

| Grade                                 | 4N         | 4N5        | ULSI 5N   |
|---------------------------------------|------------|------------|-----------|
| Purity, %                             | 99.99      | 99.995     | 99.999    |
| Oxygen                                | ≤20.0 ppmv | ≤10.0 ppmv | ≤1 ppmv   |
| Nitrogen                              | ≤50.0 ppmv | ≤20.0 ppmv | ≤1 ppmv   |
| Carbon Monoxide                       |            |            | ≤0.2 ppmv |
| Total Hydrocarbons (CH <sub>4</sub> ) |            | ≤5 ppmv    | ≤4 ppmv   |
| Water                                 |            | ≤5 ppmv    | ≤2 ppmv   |
| Hydrogen                              |            |            | ≤1 ppmv   |

• A lot analysis is provided for each order. - Individual analysis is also available upon request.

• Pneumatic valves and JIS connections are available upon request.

• A FLET (Full Length Educator Tube) is available upon request.

|          | Internal Volume   | Liters | 43.8     | 17.1  |
|----------|-------------------|--------|----------|-------|
| DER      | Cylinder Sizes >> |        | QF/QA/QB | GF/GA |
| CYLINDER | Content           | lbs    | 60       | 24    |
|          |                   | kg     | 27.2     | 10.9  |
|          | Change Point*     | lbs    | 19.56    | 7.64  |

\*Recommended Cylinder Change Point at NTP, based on Phase Break, or the amount of product left in the cylinder when the liquid phase has completely evaporated and only gaseous product is left (estimate based on ideal gas behavior).

|      | DOT Shipping Name  | Carbon Dioxide          | UN Number    | UN 1013      | Shipped as |
|------|--------------------|-------------------------|--------------|--------------|------------|
| SHIP | DOT Classification | 2.2 (Non-Flammable Gas) | ECCN #       | 1C980        | Liquefied  |
|      | DOT Label          | NON-FLAMMABLE GAS       | Harmonized # | 2811.21.0000 | Gas        |

| DATA      | Cylinder Pressure | 830 psig        |  |
|-----------|-------------------|-----------------|--|
|           | @NTP              | 59.4 atm        |  |
| L D       | Specific Volume   | 0.54 m³/kg      |  |
| R         | @NTP              | 8.74 ft³/lb     |  |
| TECHNICAL | CAS No            | 124-38-9        |  |
|           | CGA/DISS/JIS      | 320/716/W22-14R |  |
|           | Molecular Weight  | 44.01 g/mol     |  |

| Critical Temperature                      | 31°C      | 87.9°F     |  |  |
|---|-----------|------------|--|--|
| Critical Pressure                         | 72.85 atm | 1,071 psia |  |  |
| NTP = 21°C or 70°F and 101.3 kPa or 1 atm |           |            |  |  |

|          |                | Nominal Diameter (OD)xHeight* |              | Material of Construction |       |
|----------|----------------|-------------------------------|--------------|--------------------------|-------|
| Cylinder | Treatment      | cm                            | Inches       | Cylinder                 | Valve |
| QF       | ULTRA-LINE®    | 23x130/134/143                | 9x51/52.5/56 | CS                       | SS    |
| QA       | ULTRA-LINE®    | 23x130/134/143                | 9x51/52.5/56 | CS                       | Brass |
| QB       | ULTRA-LINE II® | 23x130/134/143                | 9x51/52.5/56 | CS                       | SS    |
| GF       | ULTRA-LINE®    | 23x66/70/79                   | 9x26/27.5/31 | CS                       | SS    |
| GA       | ULTRA-LINE®    | 23x66/70/79                   | 9x26/27.5/31 | CS                       | Brass |

\*Height is reported as the distance from the bottom of the cylinder to the cylinder neck/ center of the valve outlet/ top of the handwheel CS: Carbon Steel SS: Stainless Steel

▲ WARNING: This product can expose you to chemicals including Carbon Monoxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

