



Gas Mixtures – Multipurpose Two Component

Carbon Dioxide

Equipment Recommendations	Model No.
Single Stage Regulator	Series 3530-CGA*
Mini High Purity Regulator	Series 3550-180
Low Dead Volume Regulator (for Concentrations < 50ppm)	Series 3590-CGA*

Gas Mixtures

Balance Gas	Concentration Range	Matheson Mixtures Grades						Cylinder Size	CGA*	Contents		Pressure		Approximate Ship Weight	
		MR	P	C+	C	U	G			US	Metric	psig	kPa	lb	kg
Air	1 ppm - 100 ppm			•	•	•	•	1A	590	215 ft ³	6.09 m ³	2,000	13,790	133	60
								2	590	84 ft ³	2.38 m ³	2,000	13,790	74	34
								3	590	36 ft ³	1.01 m ³	2,000	13,790	39	18
								6R	180	3.73 ft ³	106 L	1,800	12,411	2	1
	100 ppm - 30 %	•	•	•	•	•	•	1A	590	215 ft ³	6.09 m ³	2,000	13,790	133	60
								2	590	84 ft ³	2.38 m ³	2,000	13,790	74	34
								3	590	36 ft ³	1.01 m ³	2,000	13,790	39	18
								6R	180	3.73 ft ³	106 L	1,800	12,411	2	1
Helium	1 ppm - 100 ppm			•	•	•	•	1A	580	202 ft ³	5.72 m ³	2,000	13,790	133	60
								2	580	79 ft ³	2.24 m ³	2,000	13,790	74	34
								3	580	34 ft ³	0.96 m ³	2,000	13,790	39	18
								6R	180	3.51 ft ³	99 L	1,800	12,411	2	1
	100 ppm - 30 %		•	•	•	•	•	1A	580	202 ft ³	5.72 m ³	2,000	13,790	133	60
								2	580	79 ft ³	2.24 m ³	2,000	13,790	74	34
								3	580	34 ft ³	0.96 m ³	2,000	13,790	39	18
								6R	180	3.51 ft ³	99 L	1,800	12,411	2	1
Hydrogen	1 ppm - 100 ppm			•	•	•	•	1A	350	200 ft ³	5.66 m ³	2,000	13,790	133	60
								2	350	78 ft ³	2.21 m ³	2,000	13,790	74	34
								3	350	33 ft ³	0.93 m ³	2,000	13,790	39	18
								6R	180	3.48 ft ³	98 L	1,800	12,411	2	1
	100 ppm - 30 %		•	•	•	•	•	1A	350	200 ft ³	5.66 m ³	2,000	13,790	133	60
								2	350	78 ft ³	2.21 m ³	2,000	13,790	74	34
								3	350	33 ft ³	0.93 m ³	2,000	13,790	39	18
								6R	180	3.48 ft ³	98 L	1,800	12,411	2	1
Nitrogen	1 ppm - 100 ppm			•	•	•	•	1A	580	213 ft ³	6.03 m ³	2,000	13,790	133	60
								2	580	83 ft ³	2.35 m ³	2,000	13,790	74	34
								3	580	35 ft ³	0.99 m ³	2,000	13,790	39	18
								6R	180	3.69 ft ³	104 L	1,800	12,411	2	1
	100 ppm - 30 %	•	•	•	•	•	•	1A	580	213 ft ³	6.03 m ³	2,000	13,790	133	60
								2	580	83 ft ³	2.35 m ³	2,000	13,790	74	34
								3	580	35 ft ³	0.99 m ³	2,000	13,790	39	18
								6R	180	3.69 ft ³	104 L	1,800	12,411	2	1
Oxygen	50 ppm - 100 ppm			•	•	•	•	1A	296	186 ft ³	5.27 m ³	1,650	11,385	133	60
								2	296	72 ft ³	2.04 m ³	1,650	11,385	74	34
								3	296	31 ft ³	0.88 m ³	1,650	11,385	39	18
								6R	180	3.56 ft ³	100 L	1,650	11,385	2	1
	100 ppm - 30 %		•	•	•	•	•	1A	296	186 ft ³	5.27 m ³	1,650	11,385	133	60
								2	296	72 ft ³	2.04 m ³	1,650	11,385	74	34
								3	296	31 ft ³	0.88 m ³	1,650	11,385	39	18
								6R	180	3.56 ft ³	100 L	1,650	11,385	2	1

Contents and pressure may vary with concentration and ambient temperature.
Certifications are traceable to NIST SRM.

Key for Matheson Mixtures Grades:

MR = Matheson Reference Standard C+ = Certified Plus Standard U = Unanalyzed Standard
P = Primary Standard C = Certified Standard G = Gravimetric Standard