



Sulfur Hexafluoride

Equipment Recommendations	Model No.
Single Stage Regulator	Series 3530-CGA*
Mini High Purity Regulator	Series 3550-180
Low Dead Volume Regulator (for Concentrations < 50ppm)	Series 3590-CGA*

Balance Gas	Concentration Range	Matheson Mixtures Grades						Cylinder Size	CGA*	Contents		Pressure		Approximate Ship Weight	
		MR	P	C+	C	U	G			US	Metric	psig	kPa	lb	kg
Helium	1 ppm - 100 ppm			•	•	•	•	1R	580	136 ft ³	3.85 m ³	2,000	13,790	70	32
								2R	580	73 ft ³	2.07 m ³	2,000	13,790	48	22
								3R	580	27 ft ³	0.77 m ³	2,000	13,790	24	11
								6R	180	3.51 ft ³	99 L	1,800	12,411	2	1
	100 ppm - 1 %			•	•	•	•	1A	580	202 ft ³	5.72 m ³	2,000	13,790	133	60
								2	580	79 ft ³	2.24 m ³	2,000	13,790	74	34
								3	580	34 ft ³	0.96 m ³	2,000	13,790	39	18
								6R	180	3.51 ft ³	99 L	1,800	12,411	2	1
Nitrogen	1 ppm - 10 ppm			•	•	•	•	1R	580	143 ft ³	4.05 m ³	2,000	13,790	70	32
								2R	580	77 ft ³	2.18 m ³	2,000	13,790	48	22
								3R	580	29 ft ³	0.82 m ³	2,000	13,790	24	11
								6R	180	3.69 ft ³	104 L	1,800	12,411	2	1
	10 ppm - 1 %			•	•	•	•	1A	580	213 ft ³	6.03 m ³	2,000	13,790	133	60
								2	580	83 ft ³	2.35 m ³	2,000	13,790	74	34
								3	580	35 ft ³	0.99 m ³	2,000	13,790	39	18
								6R	180	3.69 ft ³	104 L	1,800	12,411	2	1

Contents and pressure may vary with concentration and ambient temperature.

Key for Matheson Mixtures Grades:

MR = Matheson Reference Standard
P = Primary Standard

C+ = Certified Plus Standard
C = Certified Standard

U = Unanalyzed Standard
G = Gravimetric Standard