



n-Pentane

Equipment Recommendations	Model No.
Single Stage Regulator	Series 3530-CGA*
Mini High Purity Regulator	Series 3550-180
Low Dead Volume Regulator (for Concentrations < 50ppm)	Series 3590-CGA*

Balance Gas	Concentration Range	Matheson Mixtures Grades						Cylinder Size	CGA*	Contents		Pressure		Approximate Ship Weight	
		MR	P	C+	C	U	G			US	Metric	psig	kPa	lb	kg
Air	1 ppm - 1200 ppm		•	•	•	•	•	1A	590	215 ft ³	6.09 m ³	2,000	13,790	133	60
								2	590	84 ft ³	2.38 m ³	2,000	13,790	74	34
								3	590	36 ft ³	1.01 m ³	2,000	13,790	39	18
								6R	180	3.78 ft ³	106 L	1,800	12,411	2	1
Nitrogen	1 ppm - 1200 ppm		•	•	•	•	•	1A	350	213 ft ³	6.03 m ³	2,000	13,790	133	60
								2	350	83 ft ³	2.35 m ³	2,000	13,790	74	34
								3	350	35 ft ³	0.99 m ³	2,000	13,790	39	18
								6R	180	3.69 ft ³	104 L	1,800	12,411	2	1

Contents and pressure may vary with concentration and ambient temperature.
MTG n-Pentane certification have direct NIST Natural Gas NTRM traceability.

Key for Matheson Mixtures Grades:

MR = Matheson Reference Standard C+ = Certified Plus Standard U = Unanalyzed Standard
P = Primary Standard C = Certified Standard G = Gravimetric Standard