



n-Propyl Mercaptan

Equipment Recommendations	Model No.
Single Stage Regulator	Series 3610A-CGA
Mini High Purity Regulator	Series 3570-CGA
Low Dead Volume Regulator (for Concentrations < 50ppm)	Series 3590-CGA*
Cross Purge	4774-CGA*

Balance Gas	Concentration Range	Matheson Mixtures Grades						Cylinder Size	CGA*	Contents		Pressure		Approximate Ship Weight		
		MR	P	C+	C	U	G			US	Metric	psig	kPa	lb	kg	
Methane	1 ppm - 50 ppm			•	•			1I	350	172 ft ³	4.87 m ³	2,000	13,790	70	32	
								2I	350	92 ft ³	2.61 m ³	2,000	13,790	48	22	
								3I	350	34 ft ³	0.96 m ³	2,000	13,790	24	11	
								6I	180	4.37 ft ³	124 L	1,800	12,411	2	1	
	50 ppm - 1 %				•	•		•	1R	350	172 ft ³	4.87 m ³	2,000	13,790	70	32
									2R	350	92 ft ³	2.61 m ³	2,000	13,790	48	22
									3R	350	34 ft ³	0.96 m ³	2,000	13,790	24	11
									6R	180	4.37 ft ³	124 L	1,800	12,411	2	1
Nitrogen	500 ppb - 50 ppm			•	•			1I	350	143 ft ³	4.05 m ³	2,000	13,790	70	32	
								2I	350	77 ft ³	2.18 m ³	2,000	13,790	48	22	
								3I	350	33 ft ³	0.82 m ³	2,000	13,790	24	11	
								6I	180	3.69 ft ³	104 L	1,800	12,411	2	1	
	50 ppm - 0.1 %			•	•	•		•	1R	350	143 ft ³	4.05 m ³	2,000	13,790	70	32
									2R	350	77 ft ³	2.18 m ³	2,000	13,790	48	22
									3R	350	33 ft ³	0.82 m ³	2,000	13,790	24	11
									6R	180	3.69 ft ³	104 L	1,800	12,411	2	1

Contents and pressure may vary with concentration and ambient temperature.

Key for Matheson Mixtures Grades:

MR = Matheson Reference Standard
P = Primary Standard

C+ = Certified Plus Standard
C = Certified Standard

U = Unanalyzed Standard
G = Gravimetric Standard