



Goodyear Vintner Hose

For handling in-plant and/or tank transfer of wine.

- **Construction Tube:** White Chlorobutyl (FDA/USDA compliant and conforms to 3-A Sanitary Standard 18-03)
- **Cover:** Gray Versigard synthetic rubber (wrapped) / purple branding tape
- **Reinforcement:** Spiral-plyed synthetic fabric with Monofilament Helix
- **Temperature Range:** -30°F to 220°F
- **Packaging:** Sold per foot; maximum 100' length

Ordering Information

Part Number	Inside Diameter	Nominal Outside Diameter	Maximum Working Pressure	Bend Radius	Vacuum HG	Weight
GDY 20020354	1"	1.62"	250 psi	3"	27"	0.71 LB/FT
GDY 20020356	1-1/2"	2.11"	250 psi	4"	27"	0.98 LB/FT
GDY 20020361	2"	2.68"	250 psi	7"	27"	1.38 LB/FT



Goodyear Gorilla Wash Down Hose

A multi-purpose industrial hose for high pressure wash down.

- **Construction Tube:** Nitrile synthetic rubber, RMA Class A (High Oil Resistance)
- **Cover:** Yellow Carbryn synthetic rubber, RMA Class A (High Oil Resistance) MSHA approved
- **Reinforcement:** Spiral Flexten yarn, 2" is braided synthetic yarn
- **Temperature Range:** -20°F to 190°F
- **Packaging:** Sold per foot; maximum 500' length

Ordering Information

Part Number	Inside Diameter	Nominal Outside Diameter	Maximum Working Pressure	Bend Radius	Weight
GDY 20025701	3/4"	1.19"	500 psi	3"	0.41 LB/FT



Goodyear Horizon Wash Down Hose

A multi-purpose industrial hose for medium pressure wash down.

- **Construction Tube:** Versigard synthetic rubber, RMA class C (Limited Resistance)
- **Cover:** Red Versigard synthetic rubber
- **Reinforcement:** Spiral synthetic yarn
- **Temperature Range:** -40°F to 190°F
- **Packaging:** Sold per foot; maximum 500' length

Ordering Information

Part Number	Inside Diameter	Nominal Outside Diameter	Maximum Working Pressure	Weight
GDY 20026290	3/4"	1.12"	200 psi	0.34 LB/FT





Kanaflex 210 HFG Suction Hose

Heavy-duty food grade suction hose for bottling and pressure transfer.

- **Construction:** Produced entirely of compounds in compliance with FDA and 3-A nontoxic specifications, flexible PVC, rigid PVC helix, smooth bore, and smooth O.D.
- **Temperature Range:** -13°F to 140°F

Ordering Information

Part Number	Inside Diameter	Nominal Outside Diameter	Pitch	Minimum Bend Radius (72° F)	Working Pressure (72° F)	Vacuum Rating (72° F, in HG)	Weight	Standard Length
KAN 210HFG1	1"	1.25"	0.22"	1.9"	86 psi	29.8	0.26 LB/FT	100'
KAN 210HFG112	1-1/2"	1.82"	0.30"	2.8"	72 psi	29.8	0.44 LB/FT	100'
KAN 210HFG2	2"	2.39"	0.33"	3.9"	72 psi	29.8	0.74 LB/FT	100'
KAN 210HFG4	4"	4.53"	0.43"	9.1"	55 psi	29.8	2.01 LB/FT	100'



Kanaflex Kanaline FW Suction and Discharge Hose

Heavy-duty food grade suction and discharge hose for bottling and pressure transfer.

- **Construction:** Produced entirely of compounds in compliance with FDA and 3-A nontoxic specifications, flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, and corrugated O.D.
- **Temperature Range:** -13°F to 140°F

Ordering Information

Part Number	Inside Diameter	Nominal Outside Diameter	Pitch	Minimum Bend Radius (72° F)	Working Pressure (72° F)	Vacuum Rating (72° F, in HG)	Weight	Standard Length
KAN FW11/2	1-1/2"	2.03"	0.39"	2.5"	110 psi	28.0	0.56 LB/FT	100'
KAN FW2	2"	2.60"	0.41"	4.0"	100 psi	28.0	0.75 LB/FT	100'
KAN FW3	3"	3.70"	0.59"	6.3"	100 psi	28.0	1.20 LB/FT	100'
KAN FW4	4"	4.78"	0.65"	7.1"	75 psi	28.0	1.74 LB/FT	100'



Kanaflex Banding Coil

Food grade PVC banding coil designed to fit the corrugation of the Kanaline FW suction and discharge hose. Provides a smooth surface for banding.

Ordering Information

Part Number	Nominal Outside Diameter
KAN BANCOIL11/2	1-1/2"
KAN BANCOIL2	2"
KAN BANCOIL3	3"
KAN BANCOIL4	4"

