| Grade | ULSI 4N | ULTIMA 4N8 |
|----------------------|-----------|------------|
| Purity, % | 99.99 | 99.998 |
| Nitrogen | ≤40 ppmv | ≤5 ppmv |
| Oxygen | ≤10 ppmv | ≤2 ppmv |
| Carbon Dioxide | ≤15 ppmv | ≤1 ppmv |
| Methane | ≤2 ppmv | ≤1 ppmv |
| Water | ≤5 ppmv | ≤1 ppmv |
| Carbon Tetrafluoride | ≤5 ppmv | ≤1 ppmv |
| Other Organics | ≤100 ppmv | ≤10 ppmv |
| Carbon Monoxide | | ≤1 ppmv |
| Acidity as HF | | ≤0.1 ppmw |

[•] A lot analysis is provided for each order – Individual analysis is also available upon request.

[•] Other Organics = H₁₂, H₂₂, H₂₃, H_{134a}

| | Internal Volume | Liters | 43.8 | 17.1 | 7.3 |
|------|----------------------------|--------|------|-------|-----|
| SER. | Cylinder Sizes >> | | QF | GF | UF |
| | Cylinder Sizes >> Content | lbs | 64 | 25 | 11 |
| 5 | | kg | 29.1 | 11.35 | 5 |
| | Change Point* | lbs | 4.3 | 1.7 | 0.7 |

^{*}Recommended Cylinder Change Point at NTP, based on Phase Break, or the amount of product left in the cylinder when the liquid phase has completely evaporated and only gaseous product is left (estimate based on ideal gas behavior).

| | DOT Shipping Name | Difluoromethane | Shipped as |
|------|--------------------|---------------------|------------------|
| SHIP | DOT Classification | 2.1 (Flammable Gas) | Liquefied Gas |
| ᇰ | DOT Label | FLAMMABLE GAS | |
| | UN Number | UN 3252 | |

| Cylinder Pressure | 207 psig | | |
|-------------------|---|--|--|
| @NTP | 15.6 atm | | |
| Specific Volume | 0.45 m³/kg | | |
| @NTP | 7.2 ft³/lb | | |
| CAS No | 75-10-5 | | |
| CGA/DISS/JIS | 350/724/W22-14L | | |
| Molecular Weight | 52 g/mol | | |
| | @NTP Specific Volume @NTP CAS No CGA/DISS/JIS | | |

| Vapor Pressure | Temp, °C | 0.0 | 15.5 | 21.0 | 32.2 | 43.3 |
|-------------------|-------------|-----|------|------|------|------|
| | Press, psig | 102 | 172 | 207 | 279 | 372 |
| i iossuie | Temp, °F | 32 | 60 | 70 | 90 | 110 |

NTP = 21°C or 70°F and 101.3 kPa or 1 atm

| | | Nominal Diameter (OD)xHeight* | | Material of | Construction |
|----------|-------------|-------------------------------|--------------|-------------|--------------|
| Cylinder | Treatment | cm | Inches | Cylinder | Valve |
| QF | ULTRA-LINE® | 23x130/134/143 | 9x51/52.5/56 | CS | SS |
| GF | ULTRA-LINE® | 23x66/70/79 | 9x26/27.5/31 | CS | SS |
| UF | ULTRA-LINE® | 15x51/55/64 | 6x19/20.5/24 | CS | SS |

^{*}Height is reported as the distance from the bottom of the cylinder to the cylinder neck/ center of the valve outlet/ top of the handwheel CS: Carbon Steel SS: Stainless Steel

△WARNING: This product can expose you to chemicals including Carbon Monoxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

